



CA-IP100MW

Megapixel Wireless Day/Night Internet Camera with 2-Way Audio

Monitor your Home or Office, using Cadyce CA-IP100MW which gives Mega-Pixel resolution with two way audio. Complimentary camera management SecuGuard software monitors 64 cameras simultaneously.



- Supports IEEE 802.11n WLAN Standard
- Simultaneous multi-profile streaming
- High performing video compression (H.264) Up to 1280 x 720 pixels
- Supports NAS, FTP, Email, Voice alert, notify to HTTP/TCP servers
- Micro SD card slot for local storage
- Supports 3GPP mobile surveillance
- Advanced Complimentary software supports up to 64 Internet cameras

Items	Description
Wireless	Supports IEEE 802.11n WLAN Standard
Effective Pixels	1280 x 720 px
Lens	f: 2.6 mm
IR LED	High-light IR LED x 1 no. Supports auto/manual/schedule mode for IR LED on/off
Mechanical ICR	Yes
Video	
Video Encoder	H.264, MJPEG video compression
Video Mode	1.3M Mode (4:3) and 720p Mode (16:9)
Video Profile	Dual Stream simultaneously
Frame Rate	Up to 30fps (NTSC) / 25fps (PAL)
Region of Interest	2 Region of Interests (max. region size is 640x352)
Image Setting	AE, AWB, 3D Noise reduction, Digital WDR, Lens distortion correction (LDC), Defog, Anti-false color Exposure Value, Color Level, Brightness, Sharpness, Contrast, Mirror/Flip, Privacy Masks, Multi-language text, time and image overlay on OSD



Streaming	Streaming over UDP, TCP, HTTP, or HTTPS M-JPEG streaming over HTTP (server push) Controllable frame rate and bandwidth Constant and variable bit rate (H.264)
Audio	
Audio Encoder	RTSP: G.711 64kbps, G.726 32kbps
Audio Streaming	One-way or two-way
Audio Input/Output	Built-in MIC
Built-in speaker	
Network	
Supported Protocols	IIPv6, IPv4, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, Samba, ICMP, QoS
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, user access log
Users	8 simultaneous unicast users
Ethernet	10/100M auto negotiation.
Wireless	IEEE 802.11n
System Integration	
SDK	Open API for software integration, ONVIF (CA-IP100MW)
Alarm Triggers	PIR detector for human (far-infrared), Motion detection Camera tampering, Audio Detection
Motion Detection	Video motion detection up to 10 windows
Alarm Events	Video file upload via FTP server, Video file upload via email server, Video file upload via Samba to NAS, Notification to HTTP, and TCP server, Audio alerting output, Save video file to local mSD card, Push notify to smart phone apps
Video Buffer General	Pre and Post - Alarm Buffering
Power Supply	12V DC external power adapter
Connectors	RJ-45 10BaseT/100BaseTX, 12V DC power jack, mSD card, Factory default reset / WPS button
Indication LED	Green and Orange LEDs
Temperature	0°C to 40°C (32°F to 104°F)
Humidity	20% ~ 80% (non-condensing)
Viewing System	
OS	Windows XP, Vista, Win 7 Security
Browser	IE 6.0 or later, Firefox 2.0 or later, Safari, Google Chrome
Cell Phone	With 3GPP player
Video Player	VLC, Quick Time, Real Player, Core Player
Software	
Search & Installation	IP Wizard II
Bundled NVR Program	SecuGuard 6.x: 64 ch. multi-channel supports Tri-decoder 16 ch. video playback (synchronization) Smart & re-sizeable digital zoom. Snapshot and edit Motion, DI, Scheduler recording Fast rewind and forward (MPEG4, H.264, MJPEG rewind) 32x24 motion detection grids Smart search (by time, by motion) E-MAP Event schedule setting Remote service

Other Products:
CA-IP100M | CA-IP2250MP
CA-IP200MP | CA-IP400MP



Compatible OS...
Windows OS, Android, iOS

Package Dimensions (L X W X H):
Box: L 120mm X W 85mm X H 185mm | L 4.7 in X W 3.3 in X H 7.2 in

EAN Codes:
CA-IP100MW - 0700587952517

www.cadyce.com

Cadyce is a registered trademark. All other trademarks belong to their respective proprietors.
Copyright ©, All rights reserved.