

CA-IP2250MP

Megapixel 1.3 Outdoor (IP 66 weather proof)
Bullet type with IR LED Internet
Camera (PoE)

CA-IP2250MP is an IP 66 certified Megapixel, PoE day and night Camera which gives better picture quality and performance.



- H.264, and MJPEG encoder
- 1280 X 1024 / 1280 X 720 resolution, max 30fps
- IR LED and ICR for day and night surveillance
- Built in Power over Ethernet
- Support various protocols: RTSP, UPnP, 3GPP, HTTPS, Samba
- Event trigger action: Send to NAS, send to FTP, send to Email, Voice alert, notify to HTTP/TCP servers
- Free bundle 64ch. SecuGuard software

Items	Description
Image Device	1.3 Mega-pixel image sensor
Effective Pixels	1280 X 1024 pixels
LED Type	IR LEDs
ICR	Yes
Lens	F: 4.3mm / F: 1.8
Video Encoder	H.264 and Motion JPEG simultaneously
Video Profile	8 profiles simultaneously
Frame Rate	Up to 30 fps (NTSC) / 25 fps (PAL)
Image Setting	AE, AWB 3D Noise reduction Exposure Value, Color Level, Brightness, Sharpness, Contrast Mirror/Flip Privacy Masks Text, time and date overlay

Streaming	Simultaneously multi-profile streaming Streaming over UDP, TCP, or HTTP M-JPEG streaming over HTTP Supports 3GPP mobile surveillance Controllable frame rate and bandwidth Constant and variable bit rate (MPEG4 / H.264)
ROI	2 Windows, Free scale Region Of Interest
Network	
Supported Protocols	TCP, UDP, HTTP, SMTP, FTP, NTP, DNS, DDNS, DHCP, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, PPPoE, 3GPP, ICMP, Samba
Security	Password protection, IP address filtering, user access log
Users	20 simultaneous uni-cast users
Ethernet	10/100Mbps Auto Negotiation
PoE	802.3 af
DDNS	DIPS
System Integration	
Application (SDK)	Open API for software integration, ONVIF
Alarm Triggers	Intelligent video motion detection
Motion Detection	10-Zone video motion detection
Alarm Events	File upload via FTP or email Notification via email, HTTP, and TCP Send to NAS server (Samba)
Video Buffer	Pre and Post - Alarm buffering
Power Supply	Built in Power Over Ethernet
Connectors	RJ-45 10BaseT / 100BaseTX (PoE)
Indication LED	Green and Orange LED's
OS	Windows 2000, XP, Vista, Windows 7 / 8
Browser	IE 6.0 or later/Firefox 2.0 or later/Safari/Chrome
Cell Phone	With 3GPP player, iPhone, Android
Video Player	VLC, Quick Time, Real Player, iPhone and Android Apps

Temperature	
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	20% ~ 80% (non-condensing)

Software	
Search & Installation	IPWizard-II
Bundled NVR Program	<ul style="list-style-type: none"> • 64ch. multi-channel supports Tri-decoder • 16ch. video playback (simultaneously) • Smart digital zoom. Snapshot and edit • Motion, DI, Scheduler recording • Fast rewind and forward (MPEG4, H.264, MJPEG rewind) • 32 X 24 motion detection grids • Smart search (by motion) • Sequential search (frame by frame) • E-MAP • Event schedule setting • Remote server function: Remove live view / Remote playback / Remote setup • Multi-language support.

Other Products:
CA-IP100MW | CA-IP100M
CA-IP200MP | CA-IP400MP

Compatible OS...
Windows OS, Android, iOS

EAN Codes:
CA-IP2250MP - 0700371491420



Package Dimensions (L X W X H):
Box: L 254mm X W 200.7mm X H 152.4mm | L 10 in X W 7.9 in X H 6 in

www.cadyce.com

Cadyce is a registered trademark. All other trademarks belong to their respective proprietors. Copyright ©, All rights reserved.