



# CA-IP400MP

## Megapixel (2M) PoE Day/Night Internet Camera with 2-Way Audio

Monitor your Home or Office, using Cadyce CA-IP400MP which gives Mega-Pixel resolution with two way audio. Complimentary camera management SecuGuard software monitors 64 cameras simultaneously.



Cadyce Golden Eye App



ONVIF

Standard



Cloud Support



64 Channel  
Complimentary S/W

### Features:

- H.264, MPEG4 and MJPEG simultaneously (Tri-encoders)
- 1600\*1200 resolution, max 15fps (2M mode)
- 1280\*720 resolution, max 30fps (720P HD mode)
- Comprehensive I/O ports: MIC in, audio out, DI, DO, RS485, RJ45, mSD
- Built in IR LED and ICR for day & night surveillance without color shift, controlled by FW
- Built in Power over Ethernet
- Support various protocols: RTSP, UPnP, 3GPP, HTTPS, Samba
- Event trigger action: Send to NAS, send to FTP, send to Email, Voice alert, save to mSD card, go to preset or tour, notify to HTTP/TCP servers
- Free bundle 64ch. SecuGuard software

### Specifications:

Camera	PoE
PoE	802.3af standard
Image Device	2 Mega-pixel image sensor
Effective Pixels	1600x1200 pixels (sensor)
Lens	4.2mm
Pan & Tilt	
Pan Degree	355°
Tilt Degree	-30~90°
Manual Pan Degree	90°/ second (max); 1°/ second (min)
Manual Tilt Degree	90°/ second (max); 1°/ second (min)
Preset Points	128 preset points
Camera Tour	16 tours
IP Module	
Video	
Video Encoder	H.264, MPEG4 and MJPEG simultaneously (Tri-encoders)
Video Profile	20 profiles simultaneously
Frame Rate	Up to 15fps for 1600*1200 Up to 30fps @720p mode
Region of Interest	5 windows with selectable resolution and codec, max region size is 640x352
Image Setting	AE, AWB Noise reduction Color, brightness, sharpness, contrast Mirror/Flip 8 Privacy Masks Text, time and date overlay Simultaneously multi-profile streaming Streaming over UDP, TCP, or HTTP
Streaming	M-JPEG streaming over HTTP (server push) Supports 3GPP mobile surveillance Controllable frame rate and bandwidth Constant and variable bit rate (MPEG4 / H.264), ROI
Audio	
Audio Encoder	• RTSP: G.711 64kbps, G.726 32kbps • 3GPP: AMR

Audio Streaming	One-way or two-way
Microphone	Built-in microphone
Audio Output	Adjustable audio output gain
<b>Network</b>	
Supported Protocols	IPv4, TCP, UDP, HTTP, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, Samba, ICMP, HTTPS
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, user access log
Users	20 simultaneous unicast users
Ethernet	10/100M auto negotiation
<b>System Integration</b>	
Application	Open API for software integration
Programming Interface	ONVIF for SDK integration
Alarm Triggers	Intelligent video motion detection and external input
Motion Detection	10-zone video motion detection with included or excluded options
Alarm Events	• File upload via FTP • File upload via SMTP email • File upload via Samba to NAS • Notification via email, HTTP, and TCP • DO (Alarm output ) • Go to PT preset position • Audio alerting output • mSD card local storage
Video Buffer	Pre- and post- alarm buffering
<b>General</b>	
RAM	256MB
ROM	16MB
Power Supply	12V DC external power adapter
Power Consumption	6.5W
Connectors	• RJ-45 10BaseT/100BaseTX • 12V DC power jack • 1 alarm input and 1 output • Phone jack Audio out • Factory default reset • mSD card
Illumination LED	12 IR LEDs
Operating Temperature	0°C to 40°C (32°F to 104°F)
Operating Humidity	20% ~ 80% (non-condensing)
Dimension	H x W x D: 97x86x81 mm
<b>Viewing System</b>	
OS	Windows® XP, Vista, 7
Browser	IE 6.0 or later, Firefox 2.0 or later, Safari , Google Chrome
Cell Phone	With 3GPP player
Video Player	VLC, Quick Time, Real Player, Core Player
<b>Software</b>	
Search & Installation	IP Wizard II
Easy DDNS	DIPS™
Bundled NVR Program	64ch. SecuGuard™ • 64ch. multi-channel supports Tri-decoder 16ch. video playback (simultaneously) • Smart & scrollable digital zoom. Snapshot and edit • Motion, DI, Scheduler recording • Fast rewind and forward (MPEG4, H.264, MJPEG rewind) • 32x24 motion detection grids • Smart search (by time, by motion ) • E-MAP • Event schedule setting • Remote service • Camera tampering

## Application:



### Other Products:

CA - IP200MP | CA - IP300MP  
CA - IP100M | IP600P

### Package Contents:

CA-IP400MP | Quick Installation Guide  
Utility CD-ROM | Camera Mounting Kit  
Power Adapter (12V DC)

### Certifications:



### Compatible OS...

Windows OS  
Mac OS

### Compatible with...

All USB Type-C™ enabled devices.

### EAN Code:

CA - IP400MP - 700587952548

**Package Dimensions (L X W X H): 9 in X 6 in X 5.6 in**

**Box: L 228mm X W 152mm X H 142mm | L9 in X W6 in X H 5.6 in**

[www.cadyce.com](http://www.cadyce.com)

Cadyce is a registered trademark. All other trademarks belong to their respective proprietors. Copyright ©, All rights reserved.