

CA-WTR150

150Mbps Wireless N Travel Router

Cadyce CA-WTR150 enables you to connect computers or laptops by either wired or wireless connections to the internet, anywhere, anytime.













- Industrial Compliant Wireless LAN & LAN
- Secure Network Connection With WEP, WPA-PSK / WPA2-PSK Wireless Security
- Support multiple sessions IPSec, L2TP and PPTP
- Easy to install & Management
- Compact design with only pocket size, easy to carry every where
- Built in battery to be used in any place, even without power plug

Specifications:

Device Interface		
Wireless WAN	USB 2.0 for external HSPA modem	
Ethernet WAN/LAN	RJ-45 port, 10/100Mbps, WAN/LAN Configurable	
Antenna	PIFA internal antenna	
WPS Button	For WPS connection/ Wifi On-Off	
Reset Button	Reset router setting to factory default	
LED Indication	Power / Ethernet / USB / WiFi	
Battery	3.7V / 1700mAh Li-ION battery Compliant to NP120 form factor (35.3 x 52.8 x 11mm)	
Power Switch	Slide ON/OFF switch	
Power Jack	Power Jack, DC 5V/1A	
(WiFi)		
Standard	IEEE 802.11b/g/n (1x1) compliance	
SSID	SSID broadcast or in stealth mode	
Channel	Auto-selection, Manually	
Security	WEP, WPA-PSK, WPA2-PSK	
WPS	WPS (Wi-Fi Protected Setup)	



Functionality				
	PPP (for WCDMA/HSxPA/EVDO/Blackberry Phone)			
Wireless WAN	Wifi Hotspot			
	PPPoE (for iBurst)			
	DHCP Client (WM Phone)			
Ethernet WAN	PPPoE, DHCP client, Static IP, PPTP, L2TF	PPPoE, DHCP client, Static IP, PPTP, L2TP		
WAN Connection	Auto-reconnect, Dial-on-Demand, Manually			
One-to-Many NAT	Virtual server, Special application, DMZ			
SPI Firewall	IP/Service filter, URL blocking, MAC control			
DoS Protection	DoS (Deny of Service) detection and protect	DoS (Deny of Service) detection and protection		
Management	SNMP, UPnP IGD, syslog	SNMP, UPnP IGD, syslog		
Administration	Web-based UI, remote login, backup/restore setting			
Environment & Certifica	ation			
Package Information	Device dimension (mm)	107 x 76 x 21		
	Package dimension (mm)	198x145x68		
	Package weight (g)	500 g		
Operation Temp.	Temp.: 0~40oC, Humidity 10%~90% non-condensing			
Storage Temp.	Temp.: -10~70oC, Humidity: 0~95% non-condensing			
EMI Certification	CE/FCC			
RoHS	RoHS compliance			



Package Contents

Other Products









Compatible with...

Compatible OS...

Box: L 107mm X W 76mm X H 21mm **L** 4 in X **W** 2 in X **H** 0.82 in

EAN Code:

www.cadyce.com